

DECLARATION OF PERFORMANCE N. CPR-DE1/9042

- 1) Unique identification code of the product-type:
Rasco SAM with vulcanisation strip (Thickness 1.5 mm)
- 2) Intended uses:
Cold self-adhesive polymer bitumen membrane for waterproofing
- 3) Manufacturer:
**Rasco Bitumentchnik GmbH, Otto-von-Guericke-Ring 11, 65205 Wiesbaden,
www.bitumentchnik.de**
- 4) Systems of AVCP:
**System 3
System 3 (for reaction to fire)**
- 5) Harmonized standards: **EN 14967:2006**

Notified bodies:

The notified body Materialprüfungsamt für das Bauwesen, TU Braunschweig, ID-No. 0761, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The notified body Materialprüfungsamt für das Bauwesen, TU Braunschweig, ID-No. . 0761 carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire	Euro Class E
Water tightness	passed
Resistance to impact-proof	proof, method A: ≤ 200 mm
Durability of water tightness after artificial aging/ decomposition	passed
Durability of water tightness against chemicals	passed
Flexibility at low temperature	≤ -30°C
Dangerous substances	none

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Holger Fleischmann – Plant manager

Augustdorf, 20.10.2015



DoP in Pdf format are available on the Rasco website.

Revision 1 notes: First issued of DoP and CE-marking

 0761	 Bitumentchnik GmbH Otto-von-Guericke-Ring 11 - 65205 Wiesbaden www.bitumentchnik.de
13 CPR-DE1/9042 EN 14967:2006 Rasco SAM with vulcanisation strip (Thickness 1.5 mm) <i>Cold self-adhesive polymer bitumen membrane for waterproofing</i>	
Reaction to fire Water tightness Resistance to impact-proof Durability of water tightness after artificial aging/ decomposition Durability of water tightness against chemicals Flexibility at low temperature Dangerous substances	Euro Class E passed proof, method A: ≤ 200 mm passed passed ≤ -30°C none

Note:

Rasco supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.