

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Holger Fleischmann – Plant manager

Augustdorf, 26.04.2017



DoP in Pdf format are available on the Rasco website.

Revision 2 notes: Product unchanged. Adjustment of sign for resistance to static loading.

 0761	 Bitumentchnik GmbH Otto-von-Guericke-Ring 11 - 65205 Wiesbaden www.bitumentchnik.de
13 CPR-DE1/9042 EN 13969:2004 + A1:2006 Rasco SAM with vulcanisation strip (Thickness 1.5 mm) <i>Cold self-adhesive polymer bitumen membrane for waterproofing</i>	
Reaction to fire	Euro Class E
Water tightness	passed
Resistance to impact-proof	proof, method: A: ≤ 200 mm
Shear resistance of joints	230 ± 80 N / 50 mm
Flexibility at low temperature	≤ -30°C
Tensile strength:	
max. tensile force: MD/CD	240 ± 40 N / 50 mm
elongation: along	370 ± 100%
across	320 ± 80%
Resistance to static loading	Proof, method: B: ≤ 5 kg
Resistance to tearing	140 ± 40 N
Durability of water tightness after artificial aging	passed
Durability of water tightness against chemicals	passed
Dangerous substances	none

Note:

Rasco supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.