

Rasco Bitumen Roof Paint

Solvent-free, fast drying paint based on bituminous emulsion. For the protection and regeneration of old weathered roofs made of fibre cement panels as well as bituminous roofing membranes and sheeting

It can be applied to roofs and areas with a minimum inclination of 3° made of fibre cement panels or bituminous roofing membranes and sheeting as well as all known and suitable mineral substrates.



PRODUCT FEATURES

- Solvent-free and environmentally friendly
- Ready to use
- Applicable with a pump/spray, roll or brush
- Frost-free at least 12 months shelf-life

TECHNICAL DATA

Consumption*	0.3-0.4 l/m ² per coat
Density	1.0 kg/l
Workable after**	20 minutes
Working and drying temperature***	+5°C to +30°C

* The consumption rates shown are minimum values. These may increase according to the manner of application.

** These times may vary greatly, depending on humidity, temperature, coating thickness and substrate. Times are based on the standard climate of + 23 °C and 50 % relative humidity.

*** Temperature: component, installation and ambient temperature.

DELIVERY UNITS

30 l bucket | 18 buckets / pallet | pallet weight approx. 580 kg

10 l bucket | 44 buckets / pallet | pallet weight approx. 485 kg

5 l bucket | 60 buckets / pallet | pallet weight approx. 350 kg

1 l bucket | 6 buckets / carton | 64 cartons / pallet | pallet weight approx. 500 kg

GENERAL NOTES

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

SUBSTRATE PREPARATION

- The substrate must be sufficiently dry, level, stable, frost-protected, clean and without traces of oil, grease, tar, honeycombing, cracks, dust, dirt, residue mortar or other potential contaminants.
- An inclination of min. 3° is necessary.

APPLICATION

- Rasco Bitumen Roof Paint is ready-to-use and can be applied evenly with a roofing brush, brush, roll or suitable spraying equipment onto the cleaned surface.
- For an optimal result, apply a minimum of 2 coats of Rasco Bitumen Roof Paint.
- The second coat may be applied after the first coat has dried thoroughly.

SPECIAL NOTES

- Protect the newly applied coat from rain, frost and strong sun light until completely dry.
- Further information regarding Rasco systemic products may be found on our website <http://www.rasco-bitumen.com/>.
- Please note the Safety Data Sheet (accessible at <http://www.rasco-bitumen.com/>)

Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 03: This document has been updated with respect to smaller editorial changes. When this version is updated it will lose its validity.