

Rasco SAM Primer Special

Solvent-free, adhesion improving primer based on bitumen emulsion for use with all Rasco waterproofing membranes

It can be applied to vertical and horizontal surfaces, foundation slabs, foundations and cellar walls. Can be used on all known and suitable mineral substrates.



PRODUCT FEATURES

- Solvent-free and environmentally friendly
- Ready to use
- Applicable with a pump/spray, roll or brush
- Easy processing
- Rapid drying
- Frost-free at least 18 months shelf-life

TECHNICAL DATA

Consumption*	0.10-0.15 l/m ²
Density	1.0 kg/l
Workable after**	45 minutes
Working and drying temperature***	+10°C to +45°C

* The consumption rates shown are minimum values. These may increase according to the manner of application.

** These times may vary greatly, depending on humidity, temperature, coating thickness and substrate. Times are based on the standard climate of + 23 °C and 50 % relative humidity.

*** Temperature: component, installation and ambient temperature.

DELIVERY UNITS

30 l bucket | 18 buckets / pallet | pallet weight: approx. 580 kg

10 l bucket | 44 bucket / pallets | pallet weight: approx. 480 kg

5 l bucket | 60 bucket / pallets | pallet weight: approx. 350 kg

GENERAL NOTES

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

SUBSTRATE PREPARATION

- The substrate must be sufficiently dry, level, stable, frost-protected, clean and without traces of oil, grease, tar, honeycombing, cracks, dust, dirt, residue mortar or other potential contaminants.
- Edges should be broken and inside joints rounded out with suitable material.

APPLICATION

- Rasco SAM Primer is ready to use and applicable with a wide brush, brush, roller or suitable spraying technique evenly to the prepared substrate.

SPECIAL NOTES

- Protect the newly applied primer from rain, frost and strong sun light until completely dry.
- At low temperatures in conjunction with high humidity the drying time may be delayed.
- Further information regarding **Rasco bitumen waterproofing membranes** and other systemic products may be found on our website <http://www.rasco-bitumen.com/>.
- Please note the Safety Data Sheet (accessible at <http://www.rasco-bitumen.com/>)

Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 03: This document has been updated with respect to the release of the new waterproofing standard DIN 18533. When this version is updated it will lose its validity.